


BRINKALERT PHONE: (786) 339-9840 www.brinkalert.com



ELEVATION LOADING DOCK SAFETY LIGHT INSTALLATION

SPECIFICATIONS

TRLK13: 2 SETS OF 1FT X 3FT LEDS IN RETAINERS FOR INSIDE, MOUNTING PLATE FOR ATTACHING BRACKET, DUAL LED CONTROLLER, AC SIGNAL CONVERTER PREMIUM, 12V EXTERNAL POWER SUPPLY, 4FT 22-4 SIGNAL WIRE CABLE, 4 STANDARD-DUTY WALL BRACKETS. (NO NEMA BOX IN KIT)

LED STRIPS: IP68-RATED

- 1' HORIZONTAL X 1' VERTICAL , 1' HORIZONTAL X 3' VERTICAL OR 1' HORIZONTAL AND 5' VERTICAL OPTION
- PROGRAMMABLE LED CONTROLLER
- LED LIGHTS WILL MIMIC RESTRAINT

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- 5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5414-006.

\searrow LED SAFETY LIGHT SYSTEM

TRUCK RESTRAINT LIGHT (PART 1)

5414-006

REVISION DATE 30/06/2021